
ARTIFACT SHEET

Enter artifact number below. Artifact number is application number + artifact type code (see list below) + sequential letter (A, B, C). The first		
artifact folder for an artifact type receives the letter A, the second B, etc		
Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB		
Indicate quantity of a single type of artifact received but not scanned. Cre individual artifact folder/box and artifact number for each Artifact Type.	ate	
CD(s) containing: computer program listing		
Doc Code: Computer Artifact Type Code: P		
pages of specification		
and/or sequence listing and/or table		
Doc Code: Artifact Artifact Type Code: S		
content unspecified or combined		
Doc Code: Artifact Artifact Type Code: U		
Stapled Set(s) Color Documents or B/W Photographs Doc Code: Artifact Type Code: C		
Microfilm(s) Doc Code: Artifact Type Code: F		
Video tape(s) Doc Code: Artifact Type Code: V		
Model(s) Doc Code: Artifact Type Code: M		
Bound Document(s) Doc Code: Artifact Type Code: B		
Confidential Information Disclosure Statement or Other Document marked Proprietary, Trade Secrets, Subject to Protective Order, Material Submitted under MPEP 724.02, etc. Doc Code: Artifact Type Code X	ıts	
Other, description: Doc Code: Artifact Type Code: Z		



The Commissioner of Patents and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America for the term set forth below, subject to the payment of maintenance fees as provided by law.

If this application was filed prior to June 8, 1995, the term of this patent is the longer of seventeen years from the date of grant of this patent or twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

If this application was filed on or after June 8, 1995, the term of this patent is twenty years from the U.S. filing date, subject to any statutory extension. If the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121 or 365(c), the term of the patent is twenty years from the date on which the earliest application was filed, subject to any statutory extension.

1 /

Acting Commissioner of Patents and Trademarks

Thomas & Hawking J.



9/1989 Rich et al. ... 6/1993 Young et al.

United States Patent [19]

Dillon et al.

[56]

3,167,658

3,599,629 3,602,213

3,769,974

3,807,388

4,013,067

4,091,803

4,305,401

4,350,165

4,370,984

4,380,240

[11] Patent Number:

5,891,021

[45] Date of Patent:

4,406,289 4,685,464 4,830,014

4,865,038

5,387,122

5,429,129

5,217,012 6/1993 5,249,576 10/1993 Apr. 6, 1999

128/633

128/633

128/632

439/353

128/633

128/633

9/1983 Wesseling et al. 128/670 8/1987 Goldberger et al. 128/633

Goodman et al. .

Goldberger et al

[54]	PARTIALLY RIGID-PARTIALLY FLEXIBLE ELECTRO-OPTICAL SENSOR FOR FINGERTIP TRANSILLUMINATION
[75]	Inventors: Andrew Joseph Dillon, Austin; Jeffrey Albert Secunda, Dallas; Todd Johnson Daniel, Frisco, all of Tex.
[73]	Assignee: Perdue Holdings, Inc., Dalias, Tex.
[21]	Appl. No.: 89,523
[22]	Filed: Jun. 3, 1998
[51]	Int. CL ⁶ A61B 5/00
[52]	U.S. Cl 600/310; 600/344
[58]	Field of Search 600/310, 322,
[30]	600/323, 340, 344, 473, 476

References Cited

U.S. PATENT DOCUMENTS

Smart et al. ...

Orr et al. Kresse et al.

Cartmell

4/1983 Jobsis et al. .

1/1965 Richter ..

11/1973

4/1974 3/1977

2/1983

8/1971 Gordy 8/1971 Howell et al.

Primary Examiner—Cary E. O'Connor Assistant Examiner—Eric F. Winakur Attorney, Agent, or Firm—Andrew J. Dillon


5,676,139 10/1997 Goldberger et al.

5/1989

571 ABSTRACT

A sensor is provided for transillumination of a blood-profused portion of a human fingertip. The sensor includes an opaque, semi-cylindrical substantially rigid cradle member having a photosensor mounted to a concave surface thereof such that ambient light cannot penetrate the cradle member and induce erroneous readings. A flexible planar web-like support structure is attached at one end thereof to the cradle member and includes a light source mounted within the web thereof. A repositionable adhesive coating on the concave surface of the cradle member holds the fleshy portion of a human fingertip in conformance therewith, and when the flexible planar web-like support structure is wrapped around a fingertip within the cradle member, the light source overlies the photosensor for transillumination of the fingertip.

18 Claims, 2 Drawing Sheets



250/239

128/2.05

128/2.05

128/205

128/2.05 128/2.05

128/690

128/640

128/640